

About This Product

This High Flow GE Water Filtration System fits under most kitchen or bathroom sinks and is IAPMO certified for performance. Removing 99% of lead found in the water, it also reduces chlorine taste and odor, sediment and other contaminants. A magnetic light prompts you when it's time to change the filter. The system is designed to connect to the sink's existing faucet, installation kit is included for added convenience and can be installed horizontally or vertically. Filtered water comes directly from the existing faucet without decreasing flow rates.

Highlights

- Guaranteed fit - compatible with select GE under sink filters including FQK1R
- Advanced filter - reduces lead, chlorine taste and odor, sediment, cysts, PFOA/PFOS
- Certified by IAPMO - Certified by IAPMO R&T against NSF/ANSI standard 42, 53, 372 and CSA B483.1
- 6-month filter life compatible under sink water filters last up to 6-months or 240 Gal.
- Lead removal - removes 99% of lead that may be found in consumers water.
- [Return Policy](#)
- California residents [see Prop 65 WARNINGS](#)

Product Information

Additional Resources

[Shop All GE](#)

From the Manufacturer

- [Use and Care Manual](#)
- [Instructions / Assembly](#)
- [Return Policy](#)

Internet # 322239813
Model # GXK140TNN
Store SKU # 1008387060

Specifications

Dimensions: H 11.4 in, W 3.4 in, D 3.4 in

Dimensions

Fitting size (in.)	.375 in	Product Depth (in.)	3.4 in
Product Height (in.)	11.4 in	Product Width (in.)	3.4 in

Details

Application Type	Residential	Bacteria Reduction (%)	0
Chlorine reduction (%)	97.2	Color	White
Connection Type	Inline	Contaminants Filtered	Lead, Chlorine
Copper Reduction (%)	0	Ease of Install	Easy Install
Features	No additional features	Filtration Method	Carbon Spun Fiber
Fitting style	Push to connect	Fluoride Reduction (%)	0

House Hold Size	Unspecified	Includes	Hardware, Installation kit
Iron Reduction (%)	0	Lead reduction (%)	98.7
Maximum feed water pressure (psi)	100	Maximum feed water temperature (F)	100
Maximum filtered water flow (gallons per min.)	1.5	Minimum feed water pressure (psi)	20
Minimum feed water temperature (F)	34	Number of filters included	1
Number of Stages	1 Stage	Pack Size	1
Product Weight (lb.)	2.8 lb	Reduces	Chlorine, Lead